




Diamond Diamox+ Coating Datasheet


DIAMOX+ (INDEX MATCHED ITO)

The **DIAMOX**+ coating is a multi-layer coating of quartz and metal oxides. The thickness of the quartz is carefully controlled to suppress unwanted reflection and enhance the transmission.

ITO is applied directly to the raw material substrate to the desired thickness or resistance value required. The additional index matching coating is then calculated and applied directly on top of the ITO with designated contact areas.

Detailed below are a few examples of Standard **DIAMOX** compared to **DIAMOX** + coatings.





DIAMOND COATINGS LTD.

Unit 3&4 Sterling Park, Pedmore Road, Brierley Hill, West Midlands, DY5 1TB

Tel: +44 (0) 121 550 9430 Fmail: enquiries@diamondcoatings

Email: enquiries@diamondcoatings.co.uk
Web: www.diamondcoatings.co.uk

DIAMOND COATINGS INC.

1428 N Horne St Suite 130, Gilbert, Arizona, 85233


Tel: +1 (480) 999 3456


Email: sales@diamondcoatings.com Web: www.diamondcoatings.com





Diamond Diamox+ Coating Datasheet





Other typical transmission peaks between the range of 525nm & 600nm on various substrates are listed below.

	Resistance Value	DIAMOX (std. ITO)	Diamox+ (Index Matched ITO)
Glass	50 Ohms/sq	89%	93%
Polycarbonate	20 Ohms/sq	82%	90%
Polycarbonate	50 Ohms/sq	85%	90.5%
H/C Acrylic	10 Ohms/sq	79%	85%
H/C Acrylic	50 Ohms/sq	85%	92%

DIAMOND COATINGS LTD.

Unit 3&4 Sterling Park, Pedmore Road, Brierley Hill, West Midlands, DY5 1TB

Tel: +44 (0) 121 550 9430

Email: enquiries@diamondcoatings.co.uk
Web: www.diamondcoatings.co.uk

DIAMOND COATINGS INC.

1428 N Horne St Suite 130, Gilbert, Arizona, 85233

Tel: +1 (480) 999 3456

Email: sales@diamondcoatings.com Web: www.diamondcoatings.com